

BHT

Material Safety Data Sheet

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

Trade name	BHT	
Synonyms	Butylated Hydroxytoluene; 2,6-di-tert-butyl-4-methyl phenol; 2,6-di-tert-butyl-p-cresol	
Manufacturer/Supplier	Merisol Antioxidants LLC	
Address	292 State Route 8 Oil City, PA, 16301	
Telephone	CHEMTREC North America Transportation Emergency (24-hr)	(800) 424-9300
	CHEMTREC World Wide	(703) 527-3887
	Other Emergencies (24-hr)	(814) 677 2028
	MSDS and Product Information (8:00am-4:30pm CST)	(814) 677 2028
	Health and Safety Information (8:00am-4:00pm CST)	(814) 677 2028

SECTION 2 COMPOSITION AND INFORMATION ON INGREDIENTS

<u>Components</u>	<u>CAS-No.</u>	<u>Weight %</u>
BHT	128-37-0	>=99

See Section 8 for Exposure Guidelines and Section 15 for Regulatory Classifications.

SECTION 3 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Appearance	White Solid at room temperature. Colorless liquid when melted.
Odor	Mild.
Precautions	CAUTION! MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. Contact with hot product will cause thermal burns. Provide adequate ventilation. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Material will burn in a fire. Dust may form explosive mixture in air. Take measures to prevent the build up of electrostatic charge.
Environmental precautions	Do not flush into surface water or sanitary sewer system. Low aquatic toxicity. Product is slightly soluble in water. According to the results of tests of biodegradability this product is not readily biodegradable. BHT is considered to have a moderate to high bioaccumulation potential (230-2500 (fish, 56-day test)) in aquatic species.

POTENTIAL HEALTH EFFECTS

Eyes	Contact with eyes may cause irritation.
-------------	---

BHT

Skin Slightly irritating. May cause sensitization by skin contact.

Inhalation May cause irritation of respiratory tract.

Ingestion Harmful if swallowed.

Additional advice Product dust may be irritating to eyes, skin and respiratory system.

(See Section 11 for Toxicological Information)

SECTION 4 FIRST AID MEASURES

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

Skin contact Wash off with soap and plenty of water. If skin irritation persists, call a physician. Wash contaminated clothing before re-use.

Inhalation Remove to fresh air. In the case of inhalation of aerosol/mist consult a physician if necessary.

Ingestion If accidentally swallowed obtain immediate medical attention. If conscious, drink plenty of water. Do not induce vomiting.

Additional advice There is no specific antidote. Treatment consists of support of respiratory and cardiovascular functions.

SECTION 5 FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

Flash point 118 °C 244 °F closed cup

Autoignition temperature 470 °C 878 °F

Flammable limits in air % by volume **Lower explosion limit:** No data available.
Upper explosion limit: No data available.

Fire and explosion Material will burn in a fire. Dust may form explosive mixture in air. Risks of ignition followed by flame propagation or secondary explosions shall be prevented by avoiding accumulation of dust, e.g. on floors and ledges.

Extinguishing media Water spray or fog, foam, dry chemical, CO₂.

Fire fighting instructions Wear self-contained breathing apparatus and protective suit.

BHT

Further information Evacuate personnel to safe areas. Stop source of fuel if possible. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Steps to be taken in case of spill or leak Remove all sources of ignition. Use personal protective equipment. Prevent further leakage or spillage. Avoid dust formation. Sweep up and shovel into suitable containers for disposal. Do not flush with water. Non-disposable equipment should be thoroughly decontaminated with soap and water. Do not flush into surface water or sanitary sewer system.

Spill precautions Do not contaminate any lakes, streams, ponds, groundwater or soil.

Reporting Requirements Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

SECTION 7 HANDLING AND STORAGE

Safe handling advice Avoid accumulation of dust. Provide for appropriate exhaust ventilation and dust collection at machinery. Take measures to prevent the build up of electrostatic charge. During processing, dust may form explosive mixture in air. Avoid contact with skin and eyes. Do not breathe vapours/dust. Handle in accordance with good industrial hygiene and safety practice. Keep containers tightly closed in a dry, cool and well-ventilated place.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES

Provide adequate ventilation. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

PERSONAL PROTECTIVE EQUIPMENT

Eyes When contact with liquid is possible, use a face shield and/or chemical splash goggles. Otherwise use safety glasses with side shields or goggles.

Skin Solvent-resistant gloves. Long sleeved clothing. Non-disposable equipment should be thoroughly decontaminated with soap and water.

Inhalation Use an approved organic vapor/particulate air-purifying respirator to control dust or fumes exposure.

BHT

EXPOSURE GUIDELINES

<u>Components</u>	<u>Exposure limit(s)</u>
BHT	OSHA PEL (5 mg/m ³) OSHA regulates as Nuisance Dust (Nuisance Particulates). ACGIH TLV (8-hour) (2 mg/m ³) (inhalable aerosol and/or vapor) NIOSH TWA (10-hour) (10 mg/m ³)

PEL= Permissible Exposure Limits
TLV= Threshold Limit Value
EL= Excursion Limit

TWA= Time Weighted Average (8 hr.)
STEL= Short Term Exposure Limit (15 min.)
WEEL= Workplace Environmental Exposure Level

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance Solid at room temperature. Colorless liquid when melted.

Colour White

Odour Mild.

Form crystals, pellets, molten

Boiling point/range 265 °C 509 °F

Vapour pressure < 0.01 mm Hg @ 20 °C

Vapor density 7.6

Solubility (water) slightly soluble 0.4 - 1.14 mg/l

Viscosity 3.45 cSt @ 80 °C
1.54 cSt @ 120 °C

Melting point/range 69 - 70 °C 156 - 158 °F

Density 1.01 g/cm³ @ 25 °C

LogKow 5.1

SECTION 10 STABILITY AND REACTIVITY

Conditions to avoid Stable under normal conditions. Keep away from heat and sources of ignition.

Hazardous decomposition products Combustion products include carbon dioxide, carbon monoxide and possibly other unidentified organic compounds.

Incompatibility with other materials Incompatible with strong acids and oxidizing agents.

BHT

Hazardous polymerization Hazardous polymerisation does not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

Additional Remarks

BHT Low acute toxicity. May cause sensitization by skin contact.

Eyes

BHT Slightly irritating.

Skin

BHT Irritating. May cause sensitization by skin contact.
Acute dermal LD50 (rat): > 2,000 mg/kg

Ingestion

BHT Acute oral LD50 (rat): > 2,930 mg/kg
Repeated oral exposure of laboratory animals (rats and mice) at doses greater than 25 mg/kg/day resulted in growth depression, and functional and histological changes to the lung, liver, kidneys, and thyroid.

Reproductive Effects

The only effects on reproduction in rats and mice were lower numbers of litters of ten or more pups at birth at doses of 100 mg/kg/day and above. During pregnancy, BHT had maternal effects on mice above oral doses of 240 mg/kg/day.

Carcinogenicity

BHT This product contains no carcinogenic substances.

SECTION 12 ECOLOGICAL INFORMATION

Aquatic toxicity Low aquatic toxicity.

BHT LC0 (Brachydanio rerio): 96 hours ≥ 0.57 mg/l

EC0 (Daphnia magna): 48 hours ≥ 0.17 mg/l

NOEC (S. subspicatus (algae)): 72 hours 0.4 mg/l

NOEC (Daphnia magna): 21 d 0.07 mg/l
(reproductive effects)

BHT

Biodegradation Product is slightly soluble in water. According to the results of tests of biodegradability this product is not readily biodegradable. BHT is considered to have a moderate to high bioaccumulation potential (230-2500 (fish, 56-day test)) in aquatic species.

Bioconcentration Factor (BCF)

BHT 230 - 2,500 ((fish) 56 d)
Accumulation in aquatic organisms is expected.

SECTION 13 DISPOSAL CONSIDERATIONS

Disposal methods Dispose of only in accordance with local, state, and federal regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.

Empty containers Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, triple-rinsed, properly bunged and promptly returned to a drum reconditioner, or properly disposed., Dispose of rinse water in accordance with local and national regulations.

SECTION 14 TRANSPORT INFORMATION

DOT description Not regulated in solid form; however, if shipped in molten form above 100 C, use the following description: UN3257, Elevated temperature liquid, n.o.s., 9, PG III

IATA description not regulated

IMDG Description not regulated

SECTION 15 REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

OSHA classification
Irritant, Sensitizer

TSCA Inventory Listing
Components

CAS-No.

2,6-Bis(1,1-dimethylethyl)-4-methylphenol

128-37-0

BHT

SARA 302 Status **Components**

CAS-No.

Weight %

Contains no chemicals subject to SARA 302 reporting.

SARA 311/312 Classification "Immediate (acute) health hazard"

SARA 313 Chemical **Components**

CAS-No.

Weight %

Contains no chemicals subject to SARA 313 reporting.

CERCLA Hazardous Substance **Components**

CERCLA RQ

Weight %

Contains no chemicals subject to CERCLA.

INTERNATIONAL REGULATIONS

Workplace Hazardous Materials Information System (WHMIS) Classification Toxic Material Causing Other Toxic Effects

Australian Inventory of Chemical Substances (AICS) Listing Listed on the AICS.

Japanese Minister of International Trade and Industry (MITI) Inventory Listing Listed on MITI.

Canadian Domestic Substance List (DSL) Inventory Listing Listed on the DSL.

European Inventory of Existing Commercial Chemical Substances (EINECS) Listing Listed on EINECS.

Phillipines Inventory List (PICCS) Listed on PICCS.

Korean Inventory List Listed on the ECL.

China Inventory List Listed on the China inventory.

BHT

STATE REGULATIONS

California Safe Drinking Water Act (Prop 65) Listing Components

CAS-No.

Contains no chemical subject to California Prop 65.

SECTION 16 OTHER INFORMATION

HAZARD RATINGS

	<u>Health</u>	<u>Flammability</u>	<u>Reactivity</u>
HMIS	1	1	0
NFPA	1	1	0

This material is FOR INDUSTRIAL USE ONLY. The data and information contained herein are being furnished for informational purposes only, upon the express condition that each customer shall make its own assessment of appropriate use and appropriate shipping, transport and storage materials and procedures for Merisol's products. Although based on information sources which Merisol considers accurate and reliable, Merisol makes no warranty, either express or implied, including any warranties of merchantability or fitness for a particular purpose, regarding the validity of this information, the information sources upon which the same are based, or the results to be obtained, and expressly disclaims any liabilities for damages or injuries resulting from the use thereof. Compliance with all applicable federal, state, and local laws and regulations remains the responsibility of the user.